

# Force restore conf backup

X-Road 7 force restore conf backup

Meant to be used on uninitialized ss and not in cluster

From old ss

- take conf backup
- get UID from (UID is for ex. ee-dev/GOV/70009770/tehik\_dev)

```
cat /etc/xroad/gpghome/openpgp-revocs.d/<-SOME-NUMBERS->.rev | grep uid
```

On new ss slave(s)

```
/usr/share/xroad/scripts/generate_gpg_keypair.sh /etc/xroad/gpghome <-UID->
```

On new ss master

```
/usr/share/xroad/scripts/generate_gpg_keypair.sh /etc/xroad/gpghome <-UID->
su xroad
/usr/share/xroad/scripts/restore_xroad_proxy_configuration.sh -f /tmp/ss-automatic-backup-
2022_03_08_031501.gpg -F -N
```

Create cluster

[https://github.com/nordic-institute/X-Road/blob/develop/doc/Manuals/ug-ss\\_x-road\\_6\\_security\\_server\\_user\\_guide.md#132-restore-from-the-command-line](https://github.com/nordic-institute/X-Road/blob/develop/doc/Manuals/ug-ss_x-road_6_security_server_user_guide.md#132-restore-from-the-command-line)

---

Revision #1

Created 27 December 2024 20:29:26 by Admin

Updated 27 December 2024 20:29:33 by Admin